



PAH-1

Stud Welding Gun

for CD or ARC stud welding with automatic stud feeding according to current standards

Technical Data

Welding range	M3 to M8, dia. 3 to 8 mm
Stud length	8 to 30 mm
Stud material	Mild steel, stainless steel, aluminum, brass
Stroke	Adjustment range 5 mm
Welding cable	3 m
IP-Code	IP 20
Workplace noise level	> 90 dB (A) may occur during welding
Dimension L x W x H	295 x 60 x 170 mm (without cable)
Weight	1.4 kg (without cable)
Order No.	94-20-025

General Information

Application

- Especially suitable for thin sheets (at least 0.5 mm)

Process variants

- **Contact welding** (optional)
- **Gap welding**
- **Short cycle drawn arc welding**

Advantages

Structure

- Rigid casing made of impact-resistant plastic
- Slide bearing for guiding the welding piston
- Sealed welding piston guidance
- Ergonomic design
- Adjustable lift
- Stud length convertible (up to 30 mm)
- Mechanical structure tested in production
- Electronically controlled



Safety

- Secure lift adjustment (with lock nut)
- High level of security to prevent the selected settings being changed inadvertently
- Guidance system protected against spatters

Welding

- Individual adjustment options for optimum welding results
- Welding on painted sheets possible (clean, smooth and flat surfaces and grounding required)
- Manual or fully automatic stud feed possible (welding element is automatically pushed through the feed tube in the chuck)

Issue 02/11
(Technical data may change)